



SPECIFICATIONS

1. CERTIFICATIONS: ECE R10
Note: Unique components, accessories and hardware kits are not typically included in the product certification test protocols. Unless otherwise Specified, the product certification referred to herein are predicated Upon the base product model configuration.
2. FLASH MODE: 135 ± 15 FPM, DOUBLE FLASH
3. VOLTAGE (NOMINAL): 12/24 VDC
4. VOLTAGE (EXTREME): 10 to 36VDC
5. CURRENT (RMS): 1.06A (@ 10 VDC NOMINAL)
6. CURRENT (PEAK): 1.85A (@ 10 VDC NOMINAL)
7. POWER (RMS MAXIMUM): 23W (@ 24 VDC NOMINAL)
8. TEMPERATURE RANGE: -20°C (-4°F) TO 50°C (122°F)
9. CONNECTION: CIGARETTE PLUG
10. MOUNTING: MAGNETIC
11. BASE MATERIAL: ASA
12. LENS MATERIAL: POLYCARBONATE
13. PRODUCT WEIGHT: 0,8 KG (1.76lbs.)

Spezifikationen

Anschluss	Zigarrenanzünder-Stecker	EMC R10	Ja
Anzahl der Blitzmuster	1	Farbe	Grün
Anzahl der LEDs	9	Farbe Linse	Grün
Befestigung	Magnetisch	Gewicht (kg)	0,800 Kg
Bestellbar per	1	Höhe mm	142 mm
Betriebsspannung	12V - 24V	Höhenbereich	131 - 170 mm
Betriebstemperatur	-20°C / +50°C	IP-Schutzart	IP65
Durchmesser mm	148 mm	Lichtquelle	LED
ECE R65 Klasse 1	Nein	Verpackung	Weißer Schachtel mit Etikett
EMC	EMC R10		